



Options by range

	Timber	Glazing ¹¹		Ironmongery				Safety	Cills ⁸					Extended Liners	Square Bay ¹⁵	Splay Bay ¹⁵	
	Hardwood ⁹ and Softwood	External Beading	Safety Glazing ¹⁰	Finish ³	Low level Handles	Additional Ironmongery Options	Secured by Design	Escape Facility	Hardwood	Flush	Stub	Standard	Extended ¹⁴	No	Corner Posts supplied	Standard Angle	Non Standard Angles
Warwick	Yes	Yes	Yes	B,G,SC,BC	Yes	Yes ²	Yes	Yes ¹²	Optional	68 (0)	95 (27) 120 (52)	155 (87)	180 (112) 200 (132)	No	68x68	45	Yes
Hathaway	Yes	No	Yes	B,G,SC,BC	Yes	No	Yes	Yes ¹²	N/A	92 (0)	119 (27) 144 (52)	179 (87)	204 (112)	No	92x92	45	Yes
Stoneleigh	Yes	Yes	Yes	B,G,SC,BC	Yes	No	Yes	Yes ¹³	Optional	68 (0)	95 (27) 120 (52)	155 (87)	180 (112) 200 (132)	No	68x68	45	Yes
Kinward	Yes	No	Yes	G,SC,BC	Yes	Heavy Duty Sash Stops, Gold or Silver only	No	Yes ¹	As Standard	165 (0) as Standard	N/A	N/A	190 (25) 214 (49) 240 (75)	Yes ¹⁶	156x156	45	Yes
Stratford	Yes ⁴	No ⁶	Yes	G,SC,BC ⁵	No	Open out door sets include opening restrictors as standard	Yes	N/A	Optional	92 (0)	119 (27) ⁷ 144 (52) ⁷	155 (63)	N/A	N/A	N/A	N/A	N/A

Notes

- 1 Escape opening can be achieved on all windows over 580mm wide (based on equal height split)
- 2 Optional integral restrictors built into hinge or lockable face fixed restrictors available for fire escape windows
- 3 Finish options available: (Black [B]; Gold [G]; Satin Chrome [SC]; Bright Chrome [BC])
- 4 Also available in European Oak (P.O.A)
- 5 Entrance door sets to have aluminium thresholds only
- 6 Supplied with internally beaded toughened double glazing
- 7 Where stone sub cills are used
- 8 Cill dimensions provided as minimum width (as flush cill) excluding cill projection, shown in brackets()
- 9 Idigbo hardwood for stain finish and Sapele hardwood for painted finish are available on request
- 10 Safety glass should be specified where windows are situated in high risk areas to comply with Build Regulations
- 11 Toughened, laminated, leaded (square, rectangular and diamond) and obscure patterns are available as options
- 12 Available for minimum opening size of 450mmx750mm, with minimum 0.33m2 overall size. If restrictors are fitted to escape facility, Maco Autolatch type restrictors will be fitted.
- 13 Please enquire for method of opening
- 14 Extended cills are available for windows sat in tile hanging or where windows are sat back behind the brickwork
- 15 Splay or square bays can be supplied and factory assembled with mitred cills
- 16 Window liners designed to allow window frame to sit behind the brickwork within a reveal.

All dimensions in mm
 Please enquire for additional costs of options selected